

CDX SERIES 3+ OILS



PRODUCT DESCRIPTION

CDX Series 3+ Oils are a range of quality monograde engine oils, manufactured from high quality mineral oils. CDX Series 3+ Oils will provide protection from wear and corrosion in 4-stroke turbo charged and non-turbo charged indirect petrol and diesel engines where a monograde oil is specified.

APPLICATIONS

CDX Series 3+ SAE 30, 40 and 50 are suitable for use in petrol and diesel engines where this type of oil is specified. CDX Series 3+ SAE 10W, 20W and 30 are suitable for transmission and hydraulic systems in off highway uses. HD Series 3+ SAE 50 where specified is suitable for use in gearboxes.

BENEFITS

- Turbo charged and naturally aspirated petrol and diesel engines.
- Protection against wear and corrosion.

PRODUCT SPECIFICATION

Allison: C4 (SAE 10W, 20W)	ZF TE-ML 02H/03A/03C/06A/07D (SAE 20W)
API: SF/CD (SAE 30, 40, 50)	ZF TE-ML 02H/03A/03C/04B/07F (SAE 30)
Caterpillar: TO-2 (10W, 20W)	ZF TE-ML 04B (SAE 40)
MAN 270 (SAE 30, 40, 50)	ZF TE-ML 04E (SAE 50)
MB: 228.2 (SAE 30, 40, 50)	
ZF TE-ML 03B/03C/05K/21K (SAE 10W0)	

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

SAE Viscosity Grade	10W	20W	30	40	50
Specific Gravity @ 15°C	0.873	0.878	0.885	0.885	0.89
Kinematic Viscosity mm ² /s					
@40°C	37.0	61.0	92.0	134.0	190.0
@100°C	6.1	8.2	10.7	13.9	18.0
Viscosity Index (VI)	108	100	98	98	98
Pour Point °C	-25	-22	-19	-19	-15
Total Base Number mg KOH/gm	7.5	7.5	7.5	7.5	7.5
Sulphated Ash % wI	1.0	1.0	1.0	1.0	1.0

PACK SIZES

CDX Series 3+ Oils are packed in the following sizes:-

1 Litre, 5 Litre, 20 Litre, 25 Litre, 205 Litre, 208 Litre, 1000 Litre IBC, Bulk Pump Off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.