

SS10W/40 SL/CH4



PRODUCT DESCRIPTION

Semi Synthetic 10w/40 is a fuel-efficient multigrade engine oil meeting current API classifications. Semi Synthetic 10w/40 is manufactured from a balanced blend of top quality mineral and synthetic base stocks, producing high quality engine oil with the properties of semi-synthetic technology. Its naturally higher lubricity offers lower internal friction for reduced engine wear. Its low viscosity offers improved flow rates and hydraulic tappet performance during cold start and engine idling, a problem with many higher viscosity oils.

APPLICATIONS

Semi Synthetic 10w/40 is suitable for normally aspirated and turbocharged, highly stressed diesel engines and petrol engines in passenger cars and light commercials particularly modern vehicles. It is miscible with all synthetic and mineral based engine oils.

BENEFITS

- * Semi-Synthetic formulation.
- * Stay in grade properties.
- * Excellent high and low
- * temperature stability.
- * Improved fuel efficiency.
- * Improved oil consumption and emissions.
- * Superior performance over standard mineral based oils.

PRODUCT SPECIFICATION

API: SL/CH-4
ACEA: A3,B3,B4
VW: 505
MB: 228.1, 229.1,229.3
Renault RN0700, RN0710

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

KV @ 100°C (cSt)	- 13.82
KV @ 40°C (cSt)	- 95.51
Viscosity Index	- 147
Pour point (°C)	-32
TBN (mg KOH / g)	- 9.18
Flash Point COC (°C)	- 220
SG @15.6oC	0.888

PACK SIZES

SS10W/40 is packed in the following sizes:-

1 Litre, 5 Litre, 20 Litre, 25 Litre, 205 Litre, 208 Litre, 1000 Litre IBC, Bulk Pump Off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.