

SEMI SYNTHETIC 75W/90 GL5



PRODUCT DESCRIPTION

Semi Synthetic 75w/90 is a high performance heavy duty automotive gear oil. It offers higher levels of performance when compared to straight mineral oils whilst being compatible with mineral oils which enables it to be simply used as a replacement product on a drain and fill basis.

APPLICATIONS

For use in high performance manual transmissions, spiral bevel axles, high load drive axles, hypoid axles and steering units. The use of this product will often smooth and improve manual gear changes in previously "notchy" gear boxes.

BENEFITS

- long service life.
- Exceptional wear protection.
- Smoother gear selection.

PRODUCT SPECIFICATION

API GL5
MIL-L-2105D
ZF TE-ML 02
ZF TE-ML05

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

| | | |
|-------------------|---|----------|
| Viscosity @ 100°C | - | 14.4 Cst |
| @ 40°C | - | 96.0 Cst |
| Density | - | 0.885 |
| Flash Point °C | - | 200 |
| Pour Point °C | - | N/A |
| Appearance | - | Red |

PACK SIZES

Semi Synthetic 75w/90 GL5 is packed in the following sizes:-

5 Litre, 20 Litre, 25 Litre, 205 Litre, 208 Litre, 1000 Litre IBC, Bulk Pump Off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.