

product data sheet

VARCUT 4320

Dual Purpose extreme pressure cutting oil

Varcut 4320 has been developed for use on medium tensile steels and all nonferrous metals in a wide range of machinery.

Varcut 4320 contains inactive sulphur EP and lubricity additives together with antimist and anti-oxidant packages

Varcut 4320 is suitable for use as a lubricating oil where a viscosity grade of ISO 32 is required. It can be utilized in automatic lathes where cross leakage into gearboxes can occur.

Features & Benefits

- EP and lubricity additives
- Anti-misting formulation
- Light colour
- Formulated on high quality mineral oil
- Multipurpose oil
- Enhances component finish
- Can be used as a lubricating oil in certain machinery
- Medium - high viscosity oil

Varcut 4320	
Characteristic	Typical Data
Colour	Light Brown
Viscosity @40°C	32 mm ² /s
Sulphur	Yes – inactive
Ester	Yes
Specific Gravity @20°C	0.88

product data sheet

Operational Recommendations

Varcut 4320 is designed to be used as supplied.

Varcut 4320 is safe for use on most metals.

Varcut 4320 should always be stored indoors and protected from extremes of temperature.

Although this product is not classified as hazardous to health, good standards of hygiene and housekeeping should always be adopted when using any industrial oils.

A separate MSDS is available for this product. Additional advice can also be obtained from your local representative.

This publication contains information and recommendations based upon data obtained from sources considered reliable and believed to be correct, however, no warranty or guarantee is expressed or implied