

product data sheet

VARMULTI RANGE

High Quality Multifunctional Lubricants

Varmulti lubricants are specially formulated to meet requirements for industrial gearboxes, slideways, hydraulic systems and general lubrication in one product. A range of viscosity grades are available to suit a wide range of applications.

Varmulti lubricants meet the high performance levels currently achieved by conventional single function lubricants in one product. This allows rationalization of oil products resulting in cost savings from the storage space required, reduced wastage and lower inventory levels

Features & Benefits

- Multifunctional performance
- Formulated on high quality mineral oil
- Resistant to oxidation for long service life
- Offers protection against machine tool corrosion
- Prevents stick / slip on slideways allowing improved machining tolerances
- Reduction in failures due to application of wrong lubricant
- Meets or exceeds industry standards

Typical Data

Varmulti	32	46	68	100	150	220	320	460	
ISO Grade	32	46	68	100	150	220	320	460	
Viscosity @40°C	32.4	45.9	69.6	100.3	149.1	221.3	319.2	263.1	mm ² /s
Flashpoint (PMOC)	205	220	225	230	240	240	245	255	°C
Specific Gravity @20°C	0.87	0.87	0.88	0.88	0.88	0.89	0.89	0.90	

product data sheet

Operational Recommendations

Varmulti lubricants are designed to be used as supplied.

Varmulti lubricants should always be stored indoors and protected from extremes of temperature.

Although this product is not classified as hazardous to health, good standards of hygiene and housekeeping should always be adopted when using any industrial oils.

A separate MSDS is available for this product. Additional advice can also be obtained from your local representative.

This publication contains information and recommendations based upon data obtained from sources considered reliable and believed to be correct, however, no warranty or guarantee is expressed or implied