

SYNTHETIC

504,507 5W/30



PRODUCT DESCRIPTION

Synthetic 504,507 5W/30 is a new generation fully synthetic super multi-grade oil suitable for the latest technology petrol and diesel engines. Synthetic 504,507 5W/30 has been developed to enable outstanding performance to be provided along with effective emission control and full compatibility with emission control after treatment systems. MID - SAPS (sulphated ash phosphorus and sulphur) additive technology ensure optimum performance of emission control equipment including particulate filters, at the same time providing long term emission system protection, ensuring a high level of continuous pollution control thereby minimising environmental damage.

APPLICATIONS

Suitable for use in most petrol and diesel engines meeting Euro IV emission standards, with or without diesel particulate filters. Particularly recommended for Volkswagens & Audis with variable service intervals (WIV) and other vehicles that require a fuel efficient lubricant.

BENEFITS

- * Effective environmental protection
- * Ensures lubricant performance over extended drain intervals
- * Effective fuel efficiency
- * Very high standards of engine cleanliness
- * Long term anti-wear and oxidation stability
- * Excellent high and low temperature performance
- * Long term additive performance

PRODUCT SPECIFICATION

API: SM/CF
ACEA: C3
BMW: LL-04
MB: 229.51
Porsche: C30

VW: 504.00, 507.00

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

KV @ 100°C (cSt)	11.8
KV @ 40°C (cSt)	71
Viscosity Index	159
Pour point (°C)	-45
Flash Point COC (°C)	200
CCS @ -30oC (CP)	6100

PACK SIZES

FS 5W/30 504,507 is packed in the following sizes:-

1 Litre, 5 Litre, 20 Litre, 25 Litre, 205 Litre, 208 Litre, 1000 Litre IBC, Bulk Pump Off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.