

COMPRESSOR OILS



PRODUCT DESCRIPTION

A range of premium quality industrial compressor lubricants. Compressor range is blended from special base oils which have low carbon forming tendencies and are fortified with additives to inhibit wear, corrosion, oxidation and foaming

APPLICATIONS

Suitable for use in rotary screw, vane and reciprocating compressors. These products can be used for extended drain intervals up to 4000 hours.

BENEFITS

- Prolonged service life due to good oxidation resistance, excellent anti-wear and anti-corrosion properties
- Low foaming tendencies
- Good demulsifiability

TYPICAL TEST DATA

ISO Viscosity Grade	-	32	46	68	100	150
Specific Gravity at 16°C	-	0.870	0.875	0.878	0.883	0.888
Kinematic Viscosity mm ² /S						
@40°C	-	32.0	46.0	68.0	100.0	150.0
@100°C	-	5.4	6.8	8.7	11.5	15.2
Viscosity Index (VI)	-	102	100	100	100	100
Pour Point °C	-	-20	-20	-20	-20	-20
Flash Point °C	-	220	230	235	245	255

PACK SIZES

Compressor oil is packed in the following sizes:-

1 Litre, 5 Litre, 20 Litre, 25 Litre, 205 Litre, 208 Litre, 1000 Litre IBC, Bulk Pump Off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.