

AIRLINE OIL 22



PRODUCT DESCRIPTION

Airline Oils are high quality oils with a naturally high viscosity index, it is intended for the lubrication of pneumatic tools, valves and related equipment. It has a low pour point and special additives to protect against rust, corrosion and water washing. Airline Oils are intended for use in systems where it may be necessary to draw off any separated water.

Airline Oils are formulated to ensure the quick creation of mist for the lubrication of downstream pneumatic equipment and exhibits low foaming tendencies.

APPLICATIONS

Airline Oils are recommended for use in air tools of most types including road drills, jack hammers, air speed saws and torque wrenches.

It is also recommended for air motors and the lubrication of pneumatic rams and cylinders. In addition, Airline Oils can be used for general lubrication in industrial applications.

BENEFITS

- Excellent anti-wear properties.
- Good oxidation inhibition.
- Anti-rust.
- Anti-foam.
- Readily separates from water.

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

Kinematic Viscosity	@ 1000°C	-	4.3 cst
	@ 40°C	-	22 cst
Viscosity Index (VI)		-	95
Density @ 15°C		-	0.85
Pour Point °C		-	-10
Flash point (C.O.C)		-	>130

PACK SIZES

Airline Oil 22 is packed in the following sizes:-

5 Litre, 20 Litre, 25 Litre, 205 Litre, 208 Litre, 1000 Litre IBC, Bulk Pump Off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.