

SUPER H.V.I 15 HYDRAULIC OIL



PRODUCT DESCRIPTION

Super HVI15 Hydraulic Oil is a are high viscosity index industrial hydraulic oil formulated from a blend of high quality solvent refined mineral oil, shear stable viscosity index improver and a multipurpose hydraulic oil additive system.

APPLICATIONS

The primary applications for HVI15 Super Hydraulic Oil is machinery operating under wide temperature variations including high pressures, specifically in vane type pumps.

HVI Super 15 Hydraulic Oil is specifically recommended for Poclain excavators.

SPECIFICATIONS

Commercial Hydraulics	HD2/900
Vickers	M-2950-S
Denison	HF-0 & HF-2
DIN	51524 Part 3, 51517 Part 3, ISO 6743-4
Cincinnati Milacron	P68-70
US Steel	127

TECHNICAL DATA SHEET

BENEFITS

Anti-wear properties protect components

Lubricity increases system efficiency by reducing friction

Antifoaming characteristics

High oxidation resistance

Reduces formation of lacquers/gumming

Effective corrosion resistance helps to protect against fungal & bacterial growth

Good water separating characteristics minimize the formation of emulsions

Low temperature performance

TYPICAL PROPERTIES

ISO Viscosity Grade	15
Flash Point (°C)	150
Kinematic Viscosity @ 40°C	15
Kinematic Viscosity @ 100°C	3.81
Viscosity Index	153

PACK SIZES

Available in 1000 LTR IBC's , 205LTR , 20LTR & 5 LTR drums