

Technical Data Sheet



Semi Synthetic SUTO 10w-40

Product Code: AGR012 - Revision: 20180913

Product Description

A premium quality multi-grade high performance super universal tractor oil manufactured from high quality mineral base oils and synthetic base stocks, combined with the latest additive technology. This results in a very high performance universal oil capable of performing in severe operations conditions created by the machinery. Our oil has a very low pour point and a high viscosity index that provides minimal wear at the cold start and maximum security when temperatures rise to extremes.

Benefits

- Natural high lubricity.
- Good anti-foaming and air release properties.
- Excellent Anti-wear Protection.
- Helps reduce wet brake noise.
- Suitable for most agricultural machinery requirements.

Applications

Engine oil: Suitable for all four stroke, naturally aspirated and turbocharged diesel engines and four stroke petrol engines.

Hydraulic oil: Has good oxidation resistance, thermal stability and low temperature performance.

Transmission oil: Formulated to be used in farm tractors and other plant where the transmission contains oil immersed "wet brake systems.

Typical Test Data

Density @ 15°C	-	0.87
Flash Point (°C)	-	>190
Kinematic Viscosity cSt @ 100°C	-	13.8
Kinematic Viscosity cSt @ 40°C	-	95.5
Pour Point (°C)	-	<-35
Viscosity Index	-	148

Product Profile

ACEA	E3
API	GL-4, CG-4
Case	MS1205/1206
Caterpillar	TO-2
Ford	M2C86C, M2C134D
John Deere	J20C
MAN	271
Massey Ferguson	M1139/ 1144/ 1145/ 1143
Mercedes Benz	227.1 228.1
ZF	06B, 06C, 07B, 07D