

## TRANSMATEC EP-4 80W

**Product Code:** GTO005 | **Revision:** 20220526



Mineral oil based monograde transmission fluid.

### Available Pack Sizes



### Applications

An API GL-4 specification gear oil blended from highly refined base oils of low aromatisation and a carefully selected additive technology that contains extreme pressure additives. Ideally suited for spiral bevel gears to operate under moderate to severe conditions. Suitable for synchronised and non-synchronised manual transmissions.

Recommended by Aztec Oils as suitable for the following applications

API GL-4

### Benefits

- Excellent oxidation stability.
- Good protection against rust and corrosion.
- High level of wear protection.
- Low temperature fluidity.

### Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.88
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm/s <sup>2</sup> )	ASTM D445	62.4
Kinematic Viscosity @ 100°C (mm/s <sup>2</sup> )	ASTM D445	8.4
Pour Point (°C)	ASTM D97	<-25
Viscosity Index	ASTM D2207	104

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.