

TRANSMATEC FS-4 75W-80

Product Code: GTO041 | **Revision:** 20220913



Fully synthetic high-performance transmission oil.

Available Pack Sizes



Applications

A fully-synthetic high performance gear oil manufactured from a blend of synthetic oil, sheer stable viscosity index improvers and a multipurpose extreme pressure additive system. It offers a high level of performance when compared to straight mineral oil whilst remaining compatible with mineral oils, enabling it to be simply used as a replacement product on a drain and fill basis.

Recommended by Aztec Oils as suitable for the following applications

API GL-4
MAN 341 Type Z1, Z2, E1
Mercedes-Benz 235.5
MTF 94
MIL-L-2105
Volvo 97305, 97307
ZF TE-ML 02A, 02B, 16K

Benefits

- Compatible with most elastomers and seal materials.
- Does not foam under extreme loads.
- Superb protection against rust and corrosion.
- Low temperature fluidity.
- Offers improved shift comfort.
- Outstanding oxidation stability to provide resistance to aging.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.85
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	53
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	9.7
Pour Point (°C)	ASTM D97	-43
Viscosity Index	ASTM D2207	171

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.