

METALTEC MIRACOR 610

Product Code: RUS012 | **Revision:** 20220323



A solvent deposited short-to-medium term rust preventative.

Available Pack Sizes



Applications

A short to medium-term solvent deposited rust preventative, with powerful dewatering properties. On evaporation of the solvent this rust preventative leaves an oil protective film, which does not harden with age. Rapidly removes water from components after machining using soluble cutting fluids or following cleaning processes.

Suitability

Can be applied by brushing or spraying but its dewatering action is most effective if the articles to be protected can be immersed in a dip tank. Easily removable with good quality solvent or alkali cleaners.

Benefits

- Effective loosening seized & corroded components.
- Excellent dewatering properties.
- Low odour de-aromatised hydrocarbon solvent, increasing operator acceptance.
- Powerful inhibitors protect from corrosion.

Typical Test Data

Appearance		Straw/light brown liquid
Drying time (hours)		1 - 2
Film type		Oil
Indoor protection (months)		6
Outdoor protection (months)		3
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	2
Flash Point (°C)	ASTM D92	>62
Solids content (%)		30
Solubility		Negligible in water, soluble in oil

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.