

PRIMECUT J6

NEAT CUTTING OIL



PRODUCT DESCRIPTION

Primecut J6 is high performance, extreme pressure neat cutting oil. Designed using a sophisticated EP additive package blended together with highly refined base stock. Designed to cover a wide range of neat oil requirements.

Primecut J6 is an EP containing neat cutting oil containing extreme pressure additives, lubricity additives and carefully selected mineral oils.

The product can be used on applications including, gear cutting, grinding, honing, keyway cutting & broaching, threading, turning, drilling, milling and general purpose metal working needs.

Primecut J6 for use on high tensile steels, stainless steel and alloys.

FEATURES & BENEFITS

- ✓ High Quality Mineral Oil
- ✓ Low Aromatic Content
- ✓ Cover all materials & applications
- ✓ High Flash Point
- ✓ High Lubricity, EP and Anti-Wear Performance
- ✓ Prolonged tool life due to anti-wear technology
- ✓ Excellent Surface Finish

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

Typical data

Appearance	Amber
Odour	Mild
Flash Point (°C)	>145
Viscosity @ 40°C (cST)	7.0 typ
Extreme Pressure Additives	Yes

PACK SIZES

PRIMECUT J6 is packed in the following sizes:-

20 Litre, 205 Litre, , 1000 Litre IBC, Bulk pump off.