

# SAFETY DATA SHEET

LITHCAL 2

Page: 1

Compilation date: 28/07/2014

Revision date: 27/09/2021

Revision No: 3

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: LITHCAL 2

Product code: PC 1116

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

### 1.3. Details of the supplier of the safety data sheet

Company name: Prime Lubricants Ltd

Unit 13

Oakney Wood Ave

Selby

North Yorkshire

YO8 8FQ

United Kingdom

Tel: +44 (0)1757 706996

Email: [sales@primelubricants.co.uk](mailto:sales@primelubricants.co.uk)

### 1.4. Emergency telephone number

Emergency tel: +44 (0)113 270 5013

(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Eye Irrit. 2: H319

Most important adverse effects: Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

Label elements:

Hazard statements: H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P264: Wash hands thoroughly after handling.

[cont...]

# SAFETY DATA SHEET

LITHCAL 2

Page: 2

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P501: Dispose of contents/container to hazardous or special waste collection point.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### ZINC OXIDE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	1314-13-2	-	Aquatic Chronic 1: H410; Aquatic Acute 1: H400	1-10%

##### PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(2-ETHYLHEXYLAND ISO-BU AND ISO-PR) ESTERS, ZINC SALTS

288-917-4	85940-28-9	-	Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Chronic 2: H411	1-10%
-----------	------------	---	--	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Consult a doctor.

**Inhalation:** Not applicable.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** Not applicable.

**Delayed / immediate effects:** Continuous skin contact may cause skin sensitivity and dermatitis

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

[cont...]

# SAFETY DATA SHEET

LITHCAL 2

Page: 3

## 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. Carbon dioxide.

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Suitable packaging:** Not applicable.

### 7.3. Specific end use(s)

**Specific end use(s):** PC24: Lubricants, greases, release products.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

[cont...]

# SAFETY DATA SHEET

LITHCAL 2

Page: 4

**Hazardous ingredients:**

**ZINC OXIDE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	-	-

## DNEL/PNEC Values

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

**Engineering measures:** The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. **Skin**

**protection:** Protective clothing.

**Environmental:** No special requirement.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Grease

**Colour:** Off-white

**Odour:** Odourless

**Solubility in water:** Insoluble

**Melting point/range°C:** >150

**Flash point°C:** >200

**Autoflammability°C:** >200

**Relative density:** 0.93

### 9.2. Other information

**Other information:** Not applicable.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

# SAFETY DATA SHEET

LITHCAL 2

Page: 5

## 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Sources of ignition. Flames.

## 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### ZINC OXIDE

IPR	RAT	LD50	240	mg/kg
ORL	MUS	LD50	7950	mg/kg

**Relevant hazards for product:**

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** Not applicable.

**Delayed / immediate effects:** Continuous skin contact may cause skin sensitivity and dermatitis

**Other information:** Not applicable.

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

#### ZINC OXIDE

ALGAE	72H ErC50	.042	mg/l
DAPHNIA	48H EC50	98	µg/l
FISH	96H LC50	320	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Not biodegradable.

[cont...]

# SAFETY DATA SHEET

LITHCAL 2

Page: 6

## 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Bioaccumulation potential.

## 12.4. Mobility in soil

**Mobility:** Insoluble in water. Floats on water. Absorbed only slowly into soil.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Not applicable.

**Disposal of packaging:** Dispose of as normal industrial waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive

[cont...]

## **SAFETY DATA SHEET**

LITHCAL 2

**Page: 7**

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.