


## AGRITEC UTTO SS HD

**Product Code:** AGR022 | **Revision:** 20230316



10W-40 semi synthetic universal tractor transmission oil.

### Available Pack Sizes



### Applications

A premium semi synthetic universal transmission and hydraulic fluid, specifically designed for use in agricultural and plant transmissions, hydraulics and rear axles including oil immersed wet brakes. Using a blend of high quality base oils and exceptional additive technology to provide an advanced lubricant which demonstrates excellent performance characteristics against various stringent test requirements of major equipment manufacturers'.

### Recommended by Aztec Oils as suitable for the following applications

API GL-4  
Allison C4  
Case MS 1210  
Caterpillar TO-2  
Ford M2C86-B/C, M2C134-D  
John Deere J20C  
Massey Ferguson M1143, M1145  
ZF TE-ML 03E, 05F, 06K, 17E, 21F

### Benefits

- Allows for rationalisation of products.
- Good resistance against aeration & foaming.
- Engineered to have good oxidation resistance, thermal stability.
- Excellent brake squawk and chatter suppression.
- Exceptional anti-wear properties.
- Provides constant frictional performance.

### Typical Test Data

|  |            |        |
|--|------------|--------|
| Density @ 15°C (kg/m <sup>3</sup> )              | ASTM D4052 | 0.87   |
| Flash Point (°C)                                 | ASTM D92   | >190   |
| Kinematic Viscosity @ 40°C (mm/s <sup>2</sup> )  | ASTM D445  | 95     |
| Kinematic Viscosity @ 100°C (mm/s <sup>2</sup> ) | ASTM D445  | 13.5   |
| Pour Point (°C)                                  | ASTM D97   | -36    |
| SAE Viscosity                                    |            | 10W-40 |
| Viscosity Index                                  | ASTM D2207 | 143    |

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

## Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the equipment's maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.