

UHPD E11 15w/40 CK4



PRODUCT DESCRIPTION

A engine oil formulated to meet the lubrication requirements for the modern day diesel engine. Using an innovative additive package in combination with the highest quality synthetic base, featuring optimal viscosity in a wide temperature range, provides unrivaled anti-friction, anti-wear and anti-scuffing properties, which significantly extend the life of equipment in all, even the most extreme, operating modes in a wide range of ambient temperatures and provides significant fuel savings;

APPLICATIONS

Suitable for engines using fuelled by natural gas (LNG) and petroleum (LPG) gas. Designed for all types of heavy-duty diesel motors (long distance trucks, buses, etc.), off-road machinery (construction, mining, agricultural) and special equipment from European, American and Asian manufacturers that meet the requirements of Euro I – V and VI where a performance level of CK-4 or lower is required. When using CK-4 oils with fuels containing more than 15 ppm sulphur, make sure to follow the recommendations of the engine manufacturer for service intervals. Can be used in gasoline engines where API SL or lower performance is required.

BENEFITS

- Offers improved wear protection, and soot dispersancy.
- Excellent oxidation stability.
- The very latest industry standard ACEA E11 and API CK-4.
- Extended drain intervals.
- Ideal choice for newer mixed fleet long haul vehicles

PRODUCT SPECIFICATION

Specifications

SAE 15W-40	API CK-4	ACEA E8	ACEA E11	MB 228.31
MB 228.51	VOLVO VDS-4.5	CUMMINS CES 20086		MAN M 3775
IVECO (ACEA E6-2016)		DAF (ACEA E6-2016)		
DETROIT DIESEL DDC93K222		RENAULT RLD-3		
MACK EOS-4.5	CATERPILLAR ECF-3			

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

Physical State :	Fluid
Colour:	Yellow/brown
Density @ 15°C -	0.872
Flash Point (°C) -	220
Kinematic Viscosity cSt @ 40°C -	95
Melting point/freezing point:	-40 °C .
Boiling point or initial boiling point and boiling range	>350 °C

PACK SIZES

UHPD E11 15w/40 CK4 is packed in the following sizes:-

5 Litre, 20 Litre, 25 Litre, 205 Litre, 208 Litre, 1000 Litre IBC, Bulk pump off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.

