

ATF

Universal



PRODUCT DESCRIPTION

Formulated from highly refined paraffinic base oils with additive package designed to inhibit oxidation and offer load carrying anti-wear protection. With high VI, low pour point, good corrosion and foaming resistance and are modified to create the particular dynamic frictional properties required.

APPLICATIONS

ATF universal is suitable for use in most automatic transmissions, torque converters, power steering units and hydraulic pumps as a service fill and top up fluid.

BENEFITS

- * Suitable for most automatic transmission units
- * Good long term anti-wear characteristics
- * Suitable for most power steering units

PRODUCT SPECIFICATION

Allison C4
Caterpillar TO-2
Ford Mercon, M2C138-CJ,
M2C 166-H
GM Dexron II, IID
MB 236.1, 236.7
ZF-TE-ML 09, 11, 14

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

Viscosity Index	-	176
Viscosity @ 100 c/S	-	7.5
Viscosity @ -23°C c/S	-	2000
Viscosity @ -40°C c/S	-	22,000
Flash point °C	-	>180

TYPICAL TEST DATA

Density KG @ 15 °C-	-	0.84
Pour point °C	-	-40
Viscosity @ 40°C	-	37

PACK SIZES

ATF Universal is packed in the following sizes:-

1 Litre, 5 Litre, 20 Litre, 25 Litre, 205 Litre, 208 Litre, 1000 Litre IBC, Bulk Pump Off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.