

AUTOFARM

15W/30



PRODUCT DESCRIPTION

Autofarm 15w/30 (SUTO) is designed to cover virtually all the lubrication requirements of agricultural machinery including farm tractors. It provides excellent high and low temperature stability, high standards of engine cleanliness and good oxidation resistance. Its natural high lubricity offers lower internal friction for reduced engine wear.

APPLICATIONS

Engine oil: Autofarm 15w/30 is suitable for all four stroke, naturally aspirated and turbocharged diesel engines and four stroke petrol engines.

Hydraulic oil: Autofarm 15w/30 has good oxidation resistance, thermal stability and low temperature performance.

Transmission oil: Autofarm 15w/30 has been primarily formulated to be used in farm tractors and other plant where the transmission contains oil immersed wet brake systems.

BENEFITS

- Natural high lubricity.
- Good anti-foaming and air release properties.
- Excellent anti-wear protection.
- Helps reduce wet brake noise.
- Suitable for most agricultural machinery requirements.

PRODUCT SPECIFICATION

API CE/SF, API GL4, MIL-L-2104D, CCMC D4, DB227.1, DB228.1
 Caterpillar Series 3, ZF TE-ML-06 + 07
 MIL-L-2105, Ford M2C 159 B2, Ford ESE-N2C-86A/B, ESN-86A/B, MF 1127A,
 M2C 134D, MF 1135, MF 1139, MF 1144, MF 1145,
 John Deere J20A, JD 303, J14B and JDM-J27A, Case MS 1206. IH B6. Allison C4. API GL4 (L-20)

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

Kinematic Viscosity	@ 100°C	-	11.4 cst
	@ 40°C	-	82 cst
Viscosity Index (VI)		-	129
TBN		-	10
Density @ 15°C		-	0.887
Pour Point °C		-	-30
Flash point (C.O.C)		-	195
Sulphated ash wt%		-	1.5

PACK SIZES

Autofarm 15w/30 is packed in the following sizes:-

5 Litre, 20 Litre, 25 Litre, 205 Litre, 208 Litre, 1000 Litre IBC, Bulk Pump Off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.