

SEMI SYNTHETIC 5W/30



PRODUCT DESCRIPTION

Semi Synthetic 5W/30 is manufactured from a balanced blend of top quality mineral and synthetic base stocks, producing high quality engine oil with the properties of semi-synthetic technology. Its naturally higher lubricity offers lower internal friction for reduced engine wear. Its low viscosity offers improved flow rates and hydraulic tappet performance during cold start and engine idling, a problem with many higher viscosity oils. It offers excellent stay in grade performance for today's modern multi valve engines.

APPLICATIONS

Semi Synthetic 5W/30 is suitable for normally aspirated and turbocharged , petrol and diesel vehicles particularly modern vehicles. It meets many of the latest Ford requirements. It is miscible with all synthetic and mineral based engine oils.

BENEFITS

- Meets and surpasses the earlier specifications of WSS M2C 912 A1 and 913A.
- Extended drain capability.
- Excellent low temperature stability for improved flow rates.
- Improved fuel efficiency.
- Semi-synthetic formulation.

PRODUCT SPECIFICATION

API: SL/SJ/CF
 ACEA: A1, B1
 Ford: WSS M2C 913-B
 BMW: LL-FE-01
 Opel: Pass
 ILSAC: GF-2

TECHNICAL DATA SHEET

TYPICAL PROPERTIES

Specific Gravity @ 15.6°C	-	0.884
KV @ 100°C (cSt)	-	11.4
KV @ 40°C (cSt)	-	71.01
Viscosity Index	-	145
Pour point (°C)	-	-44
Flash Point COC (°C)	-	212
TBN (mg KOH / g)	-	9.2

PACK SIZES

Semi Synthetic 5W/30 is packed in the following sizes:-

1 Litre, 5 Litre, 20 Litre, 25 Litre, 205 Litre, 208 Litre, 1000 Litre IBC, Bulk Pump Off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.